

How to Apply

Full Cover Roll On



Dulux Texture Full Cover Roll On™ is a flexible acrylic texture producing a flattened render finish. This traditional render texture is able to fill and level brick mortar joints and other surface imperfections.

Dulux Texture Full Cover Roll On uses a special *Full Cover Texture Roller™* that enables higher build applications for faster delivery and levelling. Once applied by roller, the material is float trowelled and levelled to a traditional render style.



Applying 1 coat of *Dulux Texture Primer™* is recommended to condition the surface and aid application of successive coats. Areas that aren't accessible by roller, should be cut in with a brush. Apply 1 coat of *Dulux Texture Primer* with a roller and allow 4 hours dry time before applying *Dulux Texture Full Cover Roll On*.



Stir contents of *Dulux Texture Full Cover Roll On* with a broad flat paddle using an up and down scooping motion. Pour contents into a deep roller bucket or tray. Using a *Full Cover Texture Roller*, load the roller, then deliver material to the wall in vertical strips to 1/2 to 3/4 metre from the ground upwards with a smooth steady action. Avoid rolling downwards as excess material may fall from the roller. After 4-5 roller widths have been applied the levelling process should be commenced.



Levelling must continue before the skin dries. Working from the ground upwards, hold the plastic float against the surface so that the leading edge is raised and angled at approximately 45 degrees. This process can be done in pairs, with one person levelling as the other continues delivering product to the wall. Push the material across the surface to fill joints and low spots. This process should broadly distribute and level the roller applied texture before it sets.



Finishing must continue before the skin dries. Finish (float) the levelled area in circular strikes to further fill and even out material. Use harder pressure to fill low spots. Work in larger, lighter strokes as material levels out. Use a clean bucket of water and a sponge to clean and keep the plastic float moist.

NOTE: *Dulux Texture Full Cover Roll On* is applied up to 10 times thicker than normal paint with the specially designed *Full Cover Texture Roller*. First coat application over brick walls will primarily fill joints and may require subsequent application to fully hide the brick outline. Prefilling and levelling deep mortar joints with a suitable grouting, cement or render will lessen the number of coats required.

Tools Required

- Full Cover Texture Roller*, heavy duty roller frame & pole
- Plastic float trowel
- Wide application pail or roller tray
- Good quality masking film and external grade tape
- Drop sheets (disposable)

Dulux Customer Service: 13 25 25

